

10/31/00

Attorney's Docket No. 57-000406

A

PATENT APPLICATION TRANSMITTAL LETTER

Assistant Commissioner for Patents
Washington, D.C. 20231

Transmitted herewith for filing is the patent application of: STEVEN M. ASHE

Entitled: DYNAMICALLY CONFIGURABLE PRINTER AND METHOD OF USE THEREOF

Small Entity Status:

- ☐ Small Entity Statement under 37 CFR 1.27 is enclosed
☐ Small Entity Status is asserted for this application under 37 CFR 1.27

Enclosed are: ☒ Six (6) sheet/s of drawing/s
☒ An Assignment of the invention to: Minolta-QMS, Inc.
☒ Declaration

CLAIMS AS FILED

	No. Filed	No. Extra	Small Entity Rate	Non-Small Entity Rate	Charge
Total					
Claims	20	20 = 0	x \$ 9.00	x \$ 18.00	\$ 0
Indep.					
Claims	4	-3 = 1	x \$ 40.00	x \$ 80.00	\$ 80.00
Multiple Dependent Claim/s			+ \$135.00	+ \$270.00	\$ 0
Basic Fee			+ \$355.00	+ \$710.00	\$ 710.00
			Total of above Charges		\$ 790.00
			Total Fee		\$ 790.00


A check/s in the amount/s of \$ 790.00 is/are enclosed to cover the filing fee
and \$40.00 to cover the Assignment recordal fee.

The Commissioner is hereby authorized to charge payment of any additional filing fees required under 37 CFR 1.16 or patent application processing fees under 37 CFR 1.17 associated with this communication to Deposit Account No. 23-0650. Please refund any overpayment to Deposit Account No. 23-0650.

An original and two copies of this sheet are enclosed.

October 30, 2000
Date

By



David C. Hanson
Attorney for Applicant
Registration No. 23,024
700 Koppers Building
436 Seventh Avenue
Pittsburgh, PA 15219-1818
Telephone: 412-471-8815
Facsimile: 412-471-4094

10/30/00
JC955 U.S. PTO

10/30/00
JC926 U.S. PTO
09/699885

09699885 10/30/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE PATENT APPLICATION OF:

ATTORNEY'S DOCKET NUMBER

STEVEN M. ASHE

57-000406

ENTITLED:

"DYNAMICALLY CONFIGURABLE PRINTER AND METHOD OF USE THEREOF"

Box Patent Application
Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" Label Number **EL561514382US**

Date of Deposit October 30, 2000

I hereby certify that the following attached papers or fees

Patent Application (22 pp.); Specification (15 pp.); 20 claims, 4 independent (6 pp.); Abstract (1 p.); Six (6) sheets drawings; Declaration and Power of Attorney (2 pp.); Assignment (1 p.); Recordation Form Cover Sheet - Patents Only (1 p.); Patent Application Transmittal Letter (1 p. in trip.); check in the amount of \$790.00 for filing fee; check in the amount of \$40.00 for Assignment recordal fee

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Tamara S. Seelnacht

(Typed name of person mailing paper or fee)

Namara J. Seelbach
(Signature of person mailing paper or fee)

JUC926 U.S. PTO
 09/699885

 10/30/00

DYNAMICALLY CONFIGURABLE PRINTER AND METHOD OF USE THEREOF

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a method for configuring a printer and, more particularly, to a method for dynamically configuring a printer through the use of printer applets or printerlets which can be downloaded into the printer.

2. Description of the Prior Art

10 Prior art printers utilize a page description language (PDL) interpreter, such as Adobe PostScript or Hewlett-Packard Page Control Language (PCL), resident in nonvolatile memory, i.e., ROM, of the printer for controlling the operation thereof in accordance with a print job received by the printer from a client, such as a stand-alone computer or a computer network which interconnects the printer and one or more computers utilizing a physical medium and communications protocols known in the art.
15 A typical print job generated by a client to a printer includes PDL commands followed by print data. The PDL interpreter of the printer interprets the PDL commands received from the client and configures the printer to receive and process the print data into bitmap data which is stored in one or more page memories in volatile memory, i.e., RAM, of the printer. Once all of the bitmap data for a page memory is received thereby, the PDL
20 interpreter causes the bitmap data for the page memory to be transferred to a print engine that prints the bitmap data on a print media.

 Prior art printers include PDL interpreters that are each configured to implement a predetermined set of capabilities. Since PDL interpreters are resident in nonvolatile memories of prior art printers, the capabilities of prior art printers can only
25 be upgraded by physically replacing present nonvolatile memories with new nonvolatile memories which include new versions or revisions of PDL interpreters and/or by adding new nonvolatile memories in the form of, for example, a printer cartridge to extend the capabilities of prior art printers.

 Problems with replacing a nonvolatile memory in a printer include the
30 time and inconvenience for a person to replace the memory as well as the need to provide appropriate technical training to enable the person to replace the memory effectively. Another problem is the delay between the time a new version or revision of PDL is

needed, and thus ordered from the printer manufacturer, and the time the replacement and/or new nonvolatile memory arrives for installation in the printer. Still another problem is the need for one or more skilled programmers, either programmers of the printer manufacturer or aftermarket programmers, to implement new PDL code and the time required for such implementation.

It is an object of the present invention to overcome the above problems and others by providing a method of controlling a printer to implement various print configurations using a high-level interpretive language, with the functional components of the printer operating in a run-time environment of that interpretive language. It is an object of the present invention to provide a method of configuring the capabilities of a printer when a client generates a print job. It is an object of the present invention to provide a method of upgrading the capabilities of a printer and operating the printer in accordance with such upgrade when a client generates a print job. Still other objects will become apparent to those of ordinary skill in the art upon reading and understanding the following detailed description.

SUMMARY OF THE INVENTION

Accordingly, I have invented a method of controlling a printer to print data on print media. The method includes providing a printer having memory including a plurality of object oriented classes stored therein. Each object oriented class is configured to control at least one operation of the printer. The memory includes a virtual port which is associated with a physical port of the printer. At least one printerlet having at least one printer configuration instruction is received at the virtual port and each printer configuration instruction is invoked. Data is also received at the virtual input port. At least one object oriented class is invoked as a function of at least one invoked printer configuration instruction. The data is processed as a function of the at least one invoked object oriented class and the processed data is printed on print media.

The plurality of object oriented classes preferably includes a sniffer class having one or more sniffer objects for detecting the type of data received at the virtual input port; a plurality of page description language (PDL) classes, with each PDL class associated with a sniffer object; or a plurality of layout manager classes, with each manager layout class for converting the received data from a virtual page to a physical

page which is printed on the print media. Each object oriented class preferably includes one or more procedures which operate on the data received at the virtual input port with the one or more printerlets.

The method preferably includes detecting for the presence of the at least one printerlet and an incoming datastream received at the virtual input port. In response to detecting the at least one printerlet in the incoming datastream, a printerlet processing routine is invoked which reads, loads, and instantiates each printer configuration instruction in the detected printerlet. A print job class is created that includes a script for processing the data. The script includes the name of at least one object oriented class which was included in the script as a function of at least one printer configuration instruction and the data is processed in accordance with the script.

Preferably, each printer configuration instruction is an interpretative command which is translated and executed in real time.

I have also invented a printer that includes a controller configured to receive one or more printerlets and data from one or more computers connected thereto. Each printerlet includes one or more printer configuration instructions and the controller invokes each printer configuration instruction. A memory is connected to the controller. The memory includes a plurality of object oriented classes stored therein. Each object oriented class is configured to control at least one operation of the printer. A print engine is also connected to the controller to be controlled thereby to print data on print media as a function of at least one object oriented class invoked by the controller from the memory in response to the controller invoking at least one printer configuration instruction. Each object oriented class preferably includes one or more procedures which operate on the data.

Each printer configuration instruction is preferably an interpretative instruction that is translated by the controller. In response to invoking at least one translated printer configuration instruction, the controller causes a script, which is instantiated in the memory in response to the printer receiving the incoming data, to include a name of the at least one object oriented class. The controller preferably operates the print engine in accordance with the script.

I have also invented a printer connectable to one or more computers. The printer includes control means connected to one or more computers for receiving therefrom one or more printerlets and data. A computer storage means is connected to the control means and stores therein a plurality of object oriented classes invocable by the control means. Each object oriented class is configured to control at least one operation of the printer. A print means is connected to the control means. The print means prints data on print media in response to receiving commands from the control means. The control means is responsive to the one or more printerlets for causing at least one object oriented class to be invoked for processing the data. The control means processes the data as a function of the invoked object oriented class and the control means issues commands to the print means as a function of the processing of the data.

Preferably, the control means invokes a port monitor class which monitors for incoming data including printerlets and data. In response to detecting a printerlet in the incoming data, the port monitor class causes the control means to invoke an interpreter for interpreting the printerlet. The control means instantiates a print job having a script that includes the name of at least one object oriented class that was included in the script as a function of the invocation of the interpreted printerlet. The control means processes the data in accordance with the script.

As a function of the invocation of the interpreted printerlet, the control means can add to the computer storage means a new object oriented class. The control means can invoke the new object oriented class as a function data type of the data.

The control means can also invoke a port monitor class which monitors for incoming data including printerlets and data. In response to detecting a printerlet in the incoming data, the port monitor class can cause the control means to invoke an interpreter for interpreting the printerlet. As a function of the invocation of the interpreted printerlet, the control means can add to the computer storage means a new object oriented class. The control means can invoke the new object oriented class as a function of the type of data.

The control means can also instantiate a print job having a script that includes the name of at least one object oriented class that was included in the script as

a function of the invocation of the interpreted printerlet. The control means can process the data in accordance with the script.

Lastly, I have invented a method of controlling a printer that includes providing a printer having a memory including a plurality of object oriented classes stored therein, with each class configured to control at least one operation of the printer. A virtual input port in the memory is associated with a physical input port of the printer. When data is received at the virtual input port, at least one object oriented class is invoked as a function of the type of data. The data is processed as a function of the at least one invoked object oriented class and the processed data is printed on print media.

A printerlet having at least one printer configuration instruction can also be received at the virtual input port. Each printer configuration instruction can be invoked and another one of the object oriented classes can be invoked as a function of the at least one invoked printer configuration instruction.

Preferably, the present invention is implemented in the control software of the printer. This control software is implemented in the JAVA programming language which enables printer applets, or printerlets, to be sent from a client, such as stand-alone computer, computer network or from the Internet. The JAVA programming language is implemented in a run-time environment that allows for strict print job control to be achieved through a multi-threaded architecture. This allows the printer to start one thread of execution for each print job, keeping control of that job until completion.

Because the control software of the printer is implemented in the JAVA programming language, configuration of the printer can be hardware independent and the printer's functions are only limited to the extent of the printerlet received by the printer and the one or more printer configuration instruction contained in the printerlet.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram drawing of a printer in accordance with the present invention connected to a computer network and/or stand-alone computer;

Fig. 2a is a block diagram drawing of the printer of Fig. 1 including physical components and a memory having a job manager and a default configuration of object oriented classes;

Fig. 2b is a block diagram drawing of a thread of execution of a default print job class shown in Fig. 2a;

Fig. 2c is a block diagram of another thread of execution of a new print job class shown in Fig. 2a;

Fig. 3 is a block diagram drawing of the printer shown in Fig. 2a including block diagrams of a new default sniffer class, a new class of sniffer vectors and a new PDL; and

Fig. 4 is a block diagram drawing of the printer shown in Fig. 2a including a trigger and event associated with one of the port monitors and a print queue

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will be described with reference to the accompanying Figures where like reference numbers correspond to like elements.

With reference to Fig. 1, a printer 2 in accordance with the present invention includes a physical input port 4 configured to be connected to receive print instruction and data from two or more computers 6 and 8 connected to physical input port 4 via a computer network 10. The computer network 10 includes software which is installed on the two or more computers 6 and 8 and a physical link 12, such as a coaxial cable, which connects the two or more computers 6 and 8 to the physical input port 4. Alternatively, printer 2 includes a physical input port 14 configured to be connected directly to a stand-alone computer 16 via a dedicated printer cable 18. Printer 2 can also include both physical input port 4 and physical input port 14 for connection to computer network 10 via physical link 12 and stand-alone computer 16 via printer cable 18, respectively.

With reference to Fig. 2a, and with continuing reference to Fig. 1, printer 2 can receive an incoming datastream from computer network 10 and, more particularly, from physical link 12. Printer 2 can also receive an incoming datastream from stand-alone computer 16 via printer cable 18. Preferably, each incoming datastream includes data 25 and/or one or more printerlets 24 which will be described in greater detail hereinafter.

Printer 2 includes a central processing unit (CPU) 20 which operates on the incoming datastream and which controls the operation of a print engine 22 as a

name of its corresponding registered PDL, e.g., PDL 40-1. In response to receiving the name of a registered PDL, job manager 28 invokes the PDL to process data 25.

When the PDL invoked by job manager 28 completes processing data 25, job manager 28 determines the layout manager 42 to be utilized to layout the data processed by the PDL. Specifically, job manager 28 retrieves from default print job 32 the name of the layout manager 42 to be utilized and invokes this layout manager 42. For example, if default print job 32 includes the name of default layout manager 42-1, job manager 28 retrieves this name from default print job 32 and invokes default layout manager 42-1. When invoked, default layout manager 42-1 arranges the processed data 25 into a form for printing by print engine 22. Thereafter, job manager 28 causes print engine 22 to print the data 25 on print media 23 in accordance with the processing of data 25 by the invoked PDL and the arrangement of the processed data by default layout manager 42-1.

At an appropriate time, job manager 28 reads one or more default print job attributes 43 from default print job 32. In the example shown in Fig. 2a, the operation identifier 44 "expiration" has an operand 45 with a value of "1". Thus, when job manager 28 completes the thread of execution defined by default print job 32, job manager 28 deletes this instance of default print job 32.

In the examples described above in connection with Figs. 2a and 2b, the incoming datastream included only data 25. However, the incoming datastream can also include one or more printerlets 24, either alone or accompanied by data 25. A printerlet 24 corresponds to an applet in the JAVA programming language. Each printerlet 24 includes one or more printer configuration instructions, with each printer configuration instruction corresponding to a JAVA command in the JAVA programming language.

A printer configuration instruction can, without limitation, report and/or modify the print environment, perform administrative functions, change the default setup (e.g., change sniffers), query and/or manipulate resources such as print job attributes, change processing policies, change the user interface, synthesize jobs, operate as a PDL, communicate with administrative agents over a network, etc.

In order to detect a printer configuration instruction in a printerlet 24, each port monitor 34-1 through 34-3 preferably includes a corresponding JBS 36-1

through 36-3 which is invoked in response to printer 2 receiving printerlet 24. Specifically, if a virtual input port 30 receives an incoming datastream, the corresponding port monitor 34 invokes its corresponding JBS 36 to detect for the presence of a printerlet 24 in the incoming datastream. If a printerlet 24 is not detected, the port monitor 34 detecting the incoming datastream causes job manager 28 to instantiate default print job 32 and commence operation in accordance therewith. However, if a printerlet 24 is detected, the JBS 36 detecting the printerlet 24 invokes a JAVA interpreter which is included as part of job manager 28. The JAVA interpreter invokes a printerlet class loader which reads, loads and instantiates the one or more printer configuration instructions included in the printerlet 24.

With reference to Fig. 2c, and with continuing reference to Figs. 2a and 2b, in the absence of a printerlet 24, the thread of execution defined by default print job 32 only changes in response to one of the sniffer objects A1-A5 supplying the name of its corresponding PDL to job manager 28 in response to identifying the data type of data 25. For example, if sniffer A1 identifies the type of data 25, sniffer A1 supplies the name of corresponding registered PDL 40-1 to job manager 28. Similarly, if sniffer A2 identifies the type of data 25, sniffer A2 supplies the name of corresponding registered PDL 40-2 to job manager 28. To the contrary, the one or more printer configuration instructions of printerlet 24 can cause job manager 28 to extend the class of default print job 32 to form new print job 33 which has a script which utilizes a different layout manager 42, e.g., 42-9, and/or which has one or more new print job attributes 43a than default print job 32.

The one or more new print job attributes 43a can be retrieved from memory 26 or downloaded into memory 26 via one or more of the printer configuration instructions of printerlet 24. Similarly, the name of the different layout manager 42 included in new print job 33 can be: (i) obtained by job manager 28 from the names of the layout managers present in memory 26 and registered with job manager 28; (ii) included by job manager 28 in new print job 33 when a different layout manager 42 is added to memory 26 via one or more of the printer configuration instructions of printerlet 24; or (iii) formed by a printer configuration instruction of printerlet 24 which causes job

manager 28 to extend an existing class of layout manager 42 to form the new layout manager 42.

Once new print job 33 is instantiated in connection with the port monitor 34 detecting the printerlet 24 with incoming datastream, job manager 28 commences operation in accordance with the script of new print job 33 as described above in connection with Figs. 2a and 2b.

The example of new print job 33 shown in Fig. 2c includes layout manager 42-9, new print job attribute 43a having an operation identifier 44a named "expiration", and an operand 45a having a value of "50". The value "50" of operand 45a causes job manager 28 to utilize the thread of execution defined by new print job 33 for the next fifty print jobs received from the same user as the printerlet 24. This enables the next fifty print jobs received by printer 2 from the user to maintain the same print format while avoiding the need to transmit one or more new printerlets 24.

To enable job manager 28 to process the next fifty print jobs received from the same user utilizing new print job 33, a unique header to be included in the print jobs from the user is stored as another new print job attribute (not shown) of new print job 33. Thereafter, when the unique header is detected in a print job received at the virtual input port 30 associated with new print job 33, job manager 28 searches the new print job attributes of new print job 33 for a match between the unique header in the print job and the unique header stored as a new print job attribute. If a match is detected, job manager 28 utilizes new print job 33 to process the print job. If a match is not detected, however, job manager 28 instantiates and invokes default print job 32 utilizing a registered PDL 40 based upon the type of data 25 detected by a sniffer object A1-A5 of default sniffer 38.

After processing each print job from the user, job manager 28 decrements the value of operand 45a and determines whether the value of operand 45a is "0". If not, job manager 28 retains new print job 33 in memory 26. If, however, operand 45a is "0", job manager 28 deletes this instance of new print job 33.

Preferably, plural default print jobs 32 and/or new print jobs 33 can be instantiated and can reside concurrently in memory 26 for two or more incoming datastreams received at one or more virtual input ports 30. For example, job manager 28

can instantiate default print job 32 and new print job 33 for two incoming datastreams received at one virtual input port 30, e.g., 30-1, or for two incoming datastreams received at two virtual input ports 30, e.g., 30-1 and 30-3. In this example, default print job 32 is attached to, or associated with, a datastream having data 25 and new print job 33 is attached to a datastream which includes a printerlet 24, and which may also include data 25. Thereafter, job manager 28 can execute the threads of execution defined by default print job 32 and new print job 33.

Job manager 28 can also instantiate default print job 32 and a default print job 32a for two incoming datastreams having data 25 with different data types received at one virtual input port 30, e.g., 30-1. Thereafter, job manager 28 can execute the threads of execution defined by default print jobs 32 and 32a.

Furthermore, job manager 28 can instantiate default print job 32 and new print job 33 for two incoming datastreams received at one virtual input port 30, e.g., 30-1, where one incoming datastream includes only data 25 and the other incoming datastream includes a printerlet 24 and, possibly, data 25. Thereafter, job manager 28 can execute the threads of execution defined by default print job 32 and new print job 33.

Still further, job manager 28 can instantiate new print job 33 and new print job 33a for two incoming datastreams received at one virtual input port 30, e.g., 30-1, or for two incoming datastreams received at two virtual input ports 30, e.g., 30-1 and 30-2, where each incoming datastream includes a printerlet 24 and, possibly, data 25. Thereafter, job manager 28 can execute the threads of execution defined by new print jobs 33 and 33a.

With reference to Fig. 3, a printerlet 24 can also be utilized by job manager 28 to invoke a new combination of PDL 40 and layout manager 42. For example, one or more printer configuration instructions included in a printerlet 24 can cause job manager 28 to extend default sniffer 38 to include a new sniffer object A6, or can download into memory 26 a new sniffer 39 which includes plural vectors of new sniffer objects, e.g., B1-B5, or can extend default sniffer 38 to form new sniffer 39 in memory 26. New sniffer object A6 and/or new sniffer class 39 enables printer 2 to detect additional data types.

Printerlet 24 can also be utilized to add one or more new PDLs, e.g., PDL 40-6, to memory 26 and to register the one or more new PDLs with job manager 28. The new PDL 40-6 can be downloaded into memory 26 or can be formed by extending a class of a PDL 40 already in memory 26. If new PDL, e.g., 40-6, is added to memory 26 at the same time as its corresponding new sniffer object, e.g., A6, the new sniffer object will be able to supply job manager 28 with the name of the new registered PDL. For example, if new sniffer object A6 recognizes the type of data 25 received at virtual input port 30-1, new sniffer object A6 returns to job manager 28 the name of corresponding registered PDL 40-6. In response to receiving the name of a registered PDL 40-6, job manager 28 invokes PDL 40-6 to process data 25.

When PDL 40-6 completes processing data 25, job manager 28 invokes default layout manager 42-1 which causes job manager 28 to arrange the processed data 25 into a form for printing by print engine 22. Thereafter, job manager 28 causes print engine 22 to print the data 25 on print media 23 in accordance with the processing of data 25 by the invoked PDL and the arrangement of the processed data by default layout manager 42-1.

In addition, as discussed above, one or more printer configuration instructions included in a printerlet 24 can be utilized to create new print job 33 having the name of a layout manager 42 other than default layout manager 42-1. Thus, by creating new print job 33 having the name of a new layout manager 42, adding a new PDL 40 to memory 26 and creating new sniffer object A6 which supplies the name of the new PDL to job manager 28, new combinations of PDL 40 and layout manager 42 can be invoked to process data 25.

With reference back to Figs. 2a and 2b, as discussed above, printerlet 24 can be used to reconfigure default print job 32 to new print job 33 which includes a script different than the script defined in default print job 32. For example, if a user wishes to print graphics in thumbnail form, i.e., multiple images reduced in size to fit on one printed page, but default print job class 32 is configured to print each incoming image in full-size on separate pages, a printerlet 24 can be sent to printer 2 when the print command is issued by the user. This printerlet 24 can include one or more printer configuration instructions which reconfigure default print job 32 to new print job 33 by

replacing the name of default layout manager 42-1 with the name of a different layout manager, e.g., 42-10, specifically configured to process graphics as thumbnails.

5 Thereafter, job manager 28 invokes default sniffer 38, the PDL associated with the sniffer object which identifies the incoming data 25, layout manager 42-10 and any default print job attributes, to process the incoming data 25 into print engine data which print engine 22 prints on print media 23. When this thread of execution has run, job manager 28 deletes this instance of new print job 33.

10 With reference to Fig. 4, a printerlet 24 can also be used to program a port monitor 34-1 to execute a specific operation upon receiving certain data 25. Specifically, printerlet 24 can modify a port monitor 34, e.g., 34-1, to include a unique header data or trigger 46a and an event 46b. In response to detecting a match between header data in incoming data 25 and unique header 46a, job manager 28 invokes event 46b. For example, a client named "ABC" wishes its print jobs to have priority over anything currently in a print queue 50 managed by job manager 28. The client would send to printer 2 a printerlet 24 which modifies port monitor 34 to include unique header 46a
15 "ABC" and corresponding event 46b which causes job manager 28 to move the print job having header data "ABC" to the front of print queue 50. In response to detecting a match between header data "ABC" in incoming data 25 and unique header 46a, job manager 28 invokes event 46b which causes job manager 28 to move print job "ABC"
20 to the front of the print queue 50. This modified port monitor 34 could remain in memory 26 until printer 2 receives another printerlet 24, which modifies or deletes unique header 46a and event 46b from the modified port monitor 34 or until a value of operand 45a associated with the identifier 44a named "expiration" expires.

25 Moreover, a special type of printerlet 24 known as a ticket printerlet 24a can also be utilized to temporarily reconfigure printer 2. Specifically, in response to receiving a ticket printerlet 24a, the JAVA interpreter invokes the printerlet class loader which reads, loads and instantiates one or more printer configuration instructions included in ticket printerlet 24a. Ticket printerlet 24a causes job manager 28 to modify the script of default print job 32 or new print job 33 for the data 25 accompanying ticket
30 printerlet 24a. For example, ticket printerlet 24a can modify default print job 32 to avoid using default sniffer 38 and to process data 25 accompanying ticket printerlet 24a using

a specific PDL 40 and/or a specific layout manager 42 identified in the ticket printerlet 24a. When job manager 28 completes processing data 25 according to the modified default print job 32, job manager 28 returns the modified default print job 32 to its original state and deletes ticket printerlet 24a.

5 In this manner, ticket printerlet 24a can be utilized to temporarily reconfigure the operation of printer 2 to process data 25 accompanying the ticket printerlet 24a. Ticket printerlet 24a avoids the need to send a first printerlet 24 to modify default print job 32 or new print job 33 to process data 25 and a second printerlet 24 to return default print job 32 or new print job 33 to its original state for processing of
10 subsequently received data 25.

 As can be seen, the present invention provides a method of controlling printer 2 to implement various print configurations using a high-level interpretive language, such as JAVA, with the functional components of printer 2 operating in a run time environment of that interpretive language. The present invention also provides a
15 method of configuring the capabilities of a printer when a client generates a print job and enables upgrading of the capabilities of printer 2 and operating printer 2 in accordance with such upgrade when a client generates a print job.

 The invention has been described with reference to the preferred embodiments. Obvious modifications, combinations, and alterations will occur to others
20 upon reading and understanding the preceding detailed description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

I CLAIM:

1. A method of controlling a printer to print data on print media, the method comprising the steps of:

5 (a) providing a printer having memory including a plurality of object oriented classes stored therein, with each class configured to control at least one operation of the printer;

(b) associating a virtual input port in the memory with a physical input port of the printer;

10 (c) receiving at the virtual input port at least one printerlet having at least one printer configuration instruction;

(d) invoking each printer configuration instruction;

(e) receiving data at the virtual input port;

(f) invoking at least one object oriented class as a function of at least one invoked printer configuration instruction;

15 (g) processing the data as a function of the at least one invoked object oriented class; and

(h) printing the processed data on print media.

2. The method as set forth in claim 1, wherein each printer configuration instruction is an interpretive command.

3. The method as set forth in claim 1, wherein the plurality of object oriented classes includes at least one of:

a sniffer class having one or more sniffer objects for detecting the type of data received at the virtual input port;

5 a plurality of page description language (PDL) classes, with each PDL class associated with a sniffer object; and

a plurality of layout manager classes, with each layout manager class for converting the received data from a virtual page to a physical page which is printed on the print media.

4. The method as set forth in claim 3, wherein the plurality of layout manager classes implement at least two of the following:

straight through printing;

two-sided printing;

5 two pages of a book on a single page in landscape;

fit to page;

thumbnail;

collate;

merge two or more print jobs onto a single page;

10 N-up, where N is the number of pages printed on a single page;

print separate colors on separate pages; and

translation between software languages.

5. The method as set forth in claim 1, wherein each class includes one or more procedures which operate on the data received at the virtual input port with the one or more printerlets.

6. The method as set forth in claim 2, wherein step (d) includes the steps of:

translating each printer configuration instruction in real time; and

executing each translated printer configuration instruction in real time.

7. The method as set forth in claim 1, further including the steps of:
detecting for the presence of the at least one printerlet in an incoming datastream received at the virtual input port;

5 in response to detecting the at least one printerlet in the incoming datastream, invoking a printerlet processing routine which reads, loads and instantiates each printer configuration instruction in the detected printerlet;

creating a print job class that includes a script for processing the data, where the script includes the name of at least one object oriented class which was included in the script as a function of at least one printer configuration instruction; and

10 processing the data in accordance with the script.

8. A printer comprising:

a controller configured to receive one or more printerlets and data from one or more computers connected thereto, where each printerlet includes one or more printer configuration instructions and the controller invokes each printer configuration instruction;

a memory connected to the controller, the memory storing therein a plurality of object oriented classes each configured to control at least one operation of the printer; and

a print engine connected to the controller to be controlled thereby to print data on print media as a function of at least one object oriented class invoked by the controller from the memory in response to the controller invoking at least one printer configuration instruction.

9. The printer as set forth in claim 8, wherein:

each printer configuration instruction is an interpretive instruction that is translated by the controller;

in response to invoking at least one translated printer configuration instruction, the controller causes a script, which is instantiated in the memory in response to the printer receiving the incoming data, to include a name of the at least one object oriented class; and

the controller operates the print engine in accordance with the script.

10. The printer as set forth in claim 8, wherein the controller is connected to the one or more computers via a computer network system which is utilized to convey the one or more printerlets and data to the printer.

11. The printer as set forth in claim 8, wherein each object oriented class includes one or more procedures which operate on the data.

12. A printer connectable to one or more computers, the printer comprising:

control means connected to one or more computers for receiving therefrom one or more printerlets and data;

5 computer storage means connected to the control means and storing therein a plurality of object oriented classes invocable by the control means, each object oriented class configured to control at least one operation of the printer; and

print means connected to the control means, the print means printing data on print media in response to receiving commands from the control means, wherein:

10 the control means is responsive to the one or more printerlets for causing at least one object oriented class to be invoked for processing the data;

the control means processes the data as a function of the invoked object oriented class; and

15 the control means issues commands to the print means as a function of the processing of the data.

13. The printer as set forth in claim 12, wherein:

the control means invokes a port monitor class which monitors for incoming data including printerlets and data;

5 in response to detecting a printerlet in the incoming data, the port monitor class causes the control means to invoke an interpreter for interpreting the printerlet;

the control means instantiates a print job having a script that includes the name of at least one object oriented class that was included in the script as a function of the invocation of the interpreted printerlet; and

the control means processes the data in accordance with the script.

14. The printer as set forth in claim 13, wherein:

as a function of the invocation of the interpreted printerlet, the control means adds to the computer storage means a new object oriented class; and

5 the control means invokes the new object oriented class as a function of the data type of the data.

15. The printer as set forth in claim 12, wherein:

the control means invokes a port monitor class which monitors for incoming data including printerlets and data;

5 in response to detecting a printerlet in the incoming data, the port monitor class causes the control means to invoke an interpreter for interpreting the printerlet;

as a function of the invocation of the interpreted printerlet, the control means adds to the computer storage means a new object oriented class; and

the control means invokes the new object oriented class as a function of the data type of the data.

16. The printer as set forth in claim 15, wherein:

the control means instantiates a print job having a script that includes the name of at least one object oriented class that was included in the script as a function of the invocation of the interpreted printerlet; and

5 the control means processes the data in accordance with the script.

17. A method of controlling a printer, the method comprising the steps of:

(a) providing a printer having memory including a plurality of object oriented classes stored therein, with each class configured to control at least one operation of the printer;

(b) associating a virtual input port in the memory with a physical input port of the printer;

(c) receiving data at the virtual input port;

(d) invoking at least one object oriented class as a function of the type of data;

(e) processing the data as a function of the at least one invoked object oriented class; and

(f) printing the processed data on print media.

18. The method as set forth in claim 17, further including the steps of:
receiving at the virtual input port a printerlet having at least one printer
configuration instruction;

invoking each printer configuration instruction; and

5 invoking another one of the object oriented classes as a function of at
least one invoked printer configuration instruction.

19. The method as set forth in claim 18, further including the steps of:
detecting for the presence of a printerlet received with the data;

5 in response to detecting the printerlet, invoking a printerlet processing
routine which reads, loads, and instantiates each printer configuration instruction in the
detected printerlet;

creating a print job class that includes a script for processing the data,
where the script includes the name of the other at least one object oriented class which
was included in the script as a function of at least one printer configuration instruction;
and

10 processing the data as in accordance with the script.

20. The method as set forth in claim 17, wherein the plurality of
object oriented classes includes:


a sniffer class having one or more sniffer objects for detecting the type of
data received at the virtual input port;


5 a plurality of page description language (PDL) classes, with each PDL
class associated with a sniffer object; and

a plurality of layout manager classes, with each layout manager class for
converting the received data from a virtual page to a physical page.

[illegible]

A printer has a controller configured to receive one or more printerlets and data from one or more computers connected thereto. Each printerlet includes one or more computer configuration instructions and the controller invokes each printer configuration instruction received in a printerlet. A memory connected to the controller stores therein a plurality of object oriented classes each configured to control at least one operation of the printer. A print engine connected to the controller to be controlled thereby prints data on print media as a function of at least one object oriented class invoked by the controller from the memory in response to the controller invoking at least one printer configuration instruction.

[illegible]



32

DEFAULT PRINT JOB				
38	SNIFFER	→ DEFAULT LAYOUT MANAGER	→ DEFAULT PRINT JOB ATTRIBUTES	→
	P	42-1	expiration	← 43
	D		44	
	L		45	

P
R
I
N
T

Fig 26






Fig 2a





	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

Steven M. Ashe declares:

I am a citizen of the United States of America and a resident of the County of Boulder, the City of Boulder, and the State of Colorado, whose post-office address is 2708 South Lakeridge Trail, Boulder, Colorado 80302.

I believe myself to be the original, first and sole inventor of the improvement entitled "**Dynamically Configurable Printer and Method of Use Thereof**" which is described and claimed in the annexed specification.

I have reviewed and understand the contents of the specification, including the claims.

I do not know and do not believe that the same was ever known or used in the United States before my invention thereof; or patented or described in any printed publication in any country before my invention or more than one year prior to this application; or in public use or on sale in the United States more than one year prior to this application.

Said invention has not been patented or been made the subject of an inventor's certificate in any country foreign to the United States on an application filed by me or my legal representatives or assigns more than twelve months prior to this application.

I acknowledge my duty to disclose information of which I am aware which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations § 1.56(a).

No application for patent or inventor's certificate thereon has been filed by me or my legal representatives or assigns in any country foreign to the United States.

I declare further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

I hereby appoint William H. Logsdon, Registration No. 22,132; Russell D. Orkin, Registration No. 25,363; David C. Hanson, Registration No. 23,024; Richard L. Byrne, Registration No. 28,498; Frederick B. Ziesenheim, Registration No. 19,438; Kent E. Baldauf, Registration No. 25,826; Barbara E. Johnson, Registration No. 31,198; Paul M. Reznick, Registration No. 33,059; John W. McIlvaine, Registration No. 34,219; Michael I. Shamos, Registration No. 30,424; Blynn L. Shideler, Registration No. 35,034;

Variable	Mean	SD	Min	Max	Median	Mode	Skewness	Kurtosis	Shapiro-Wilk	Normality
Age	35.2	12.5	20	65	30	30	0.15	2.5	0.95	Normal
Gender	1.2	0.4	1	2	1	1	0.05	0.5	0.98	Normal
Marital Status	1.5	0.5	1	3	1	1	0.10	1.0	0.96	Normal
Education	12.5	2.0	9	16	12	12	0.05	2.0	0.97	Normal
Income	1500	500	500	3000	1200	1000	0.20	3.0	0.94	Normal
Occupation	1.8	0.6	1	3	1	1	0.10	1.0	0.96	Normal
Health Status	1.5	0.5	1	3	1	1	0.05	0.5	0.98	Normal
Stress Level	2.5	1.0	1	4	2	2	0.15	2.5	0.95	Normal
Life Satisfaction	3.5	1.0	1	5	3	3	0.10	1.0	0.96	Normal
Resilience	2.0	0.8	1	4	2	2	0.15	2.5	0.95	Normal
Emotional Stability	1.8	0.6	1	3	1	1	0.10	1.0	0.96	Normal
Physical Health	1.5	0.5	1	3	1	1	0.05	0.5	0.98	Normal
Mental Health	1.8	0.6	1	3	1	1	0.10	1.0	0.96	Normal
Social Support	2.0	0.8	1	4	2	2	0.15	2.5	0.95	Normal
Life Satisfaction	3.5	1.0	1	5	3	3	0.10	1.0	0.96	Normal
Resilience	2.0	0.8	1	4	2	2	0.15	2.5	0.95	Normal
Emotional Stability	1.8	0.6	1	3	1	1	0.10	1.0	0.96	Normal
Physical Health	1.5	0.5	1	3	1	1	0.05	0.5	0.98	Normal
Mental Health	1.8	0.6	1	3	1	1	0.10	1.0	0.96	Normal
Social Support	2.0	0.8	1	4	2	2	0.15	2.5	0.95	Normal

Inventor Steven M Ashe
Steven M. Ashe